

# record STA 21

record system 20 technologies for light to medium-heavy applications



# STA 21

[www.agta-record.com](http://www.agta-record.com)



**record**

your global partner for entrance solutions

MILANO



STA 21

[www.agta-record.com](http://www.agta-record.com)



**record**

your global partner for entrance solutions

## record STA 21 – remarkably inconspicuous

We designed the record STA 21 to meet the requirements of light and medium-heavy sliding door applications. Available in standard single and twin leaf sliding models, in classic or telescopic versions.

### Benefit from record system 20 cutting edge technologies

The majority of the record STA 21 components are taken from the famous record system 20, which has a thoroughly proven track record in global markets, but fitted with smaller, lighter electrical motors and a specially modified control.

The record system 20 actively communicates between operator, sensors and remote control, enabling constant monitoring of the status of individual components, further enhancing their functionality, safety and security. Our engineers pay particular attention to ensure their long, trouble-free life. Together with these core priorities of product development, it is the carefully thought-out details that make record's door systems so popular among customers. By pre-defining door movements, unnecessary triggering of opening impulses can be eliminated. Undesirable opening movements (so-called "ghosting") such as self-triggering caused by movements of the installation's own door leaves can be eliminated entirely, thanks to system 20's self-learning capabilities.

Responsible for the whisper-quiet operation typical of record products is our refined gear and roller technology, augmented by profile end guides and parts made from special low-noise plastic.

### Tasteful Design

All applications share the same profile system, which features clear, elegant lines, and an attractive overall design. These many design options allow our door systems to be integrated equally harmoniously in a building, or become a style feature.

### Approved for the highest levels of safety and security

The record STA 21 product line fulfils all relevant European and national norms and standards, including DIN 18 650, EN 16 005 and EN ISO 13 849.



D-STA 2 leaves



D-STA 2 leaves



E-TSA 2 leaves



E-TSA 2 leaves



# STA 21

[www.agta-record.com](http://www.agta-record.com)



**record**

your global partner for entrance solutions

## Designed for light to medium-heavy door applications

Based on the record system 20, the record STA 21 has been modified to meet the requirements of light to medium-heavy door applications. Both have the same system, enabling the interactive exchange of information between control, sensors and electronic remote control unit.

### The most important functions

The 32-bit microprocessor control enables a wide variety of operational modes and functions. The mode of operation is selected intuitively using the BDE-D electronic remote control; the display features text in the language of your choice. The convenient and user-friendly BDE-D remote control can also be used to set or modify application-specific door parameters such as opening and closing speeds, opening widths for reduced opening, duration of open times, etc. Alternatively, parameter setting can also be done mechanically using the robust, key-operated switch.

### Safety and security equipment

The record STA 21 can be fitted with motorized bolt locking. Fitting security floor rails with extended blades can further enhance burglar protection levels.

One optional available is manual unlocking in or outside buildings to guarantee the opening of the automatic door during power failures. Another is a rechargeable battery equipped with charging status monitoring to open or close the door in emergencies. For the French market we even supply the CO48 emergency opening system, but with some restrictions on door leaf weights.

	record STA 21 – standard sliding doors (STA)		record STA 21 – telescopic sliding doors (TSA)	
				
<b>Door models</b>	E-STA 1 leaf	D-STA 2 leaves	E-TSA 2 leaves	D-TSA 4 leaves
<b>Opening width</b>	800 – 2000 mm	800 – 2500 mm	800 – 2500 mm	1440 – 3000 mm
<b>Max. height of passage</b>	2500 mm	2500 mm	2500 mm	2500 mm
<b>Max. door leaf weight</b>	1 x 120 kg *	2 x 75 kg *	2 x 80 kg *	4 x 50 kg *
<b>Recommended application</b>	For light duties in tight spaces	For functional entrances with large entrance widths	For maximum entrance widths in tight spaces	For elegant entrances with large entrance widths

\* In line with examination certificate; up to 20% higher weights possible at reduced acceleration levels



D-STA 2 leaves



E-STA 1 leaf

Door applications	record STA 21	record STA 20	Special door automation
Standard sliding doors with 1 or 2 leaves	●	●	record STA 22 – STA
Telescopic sliding doors with 2 or 4 leaves	●	●	record STA 22 – TSA
Sliding doors with break-out system		●	
Round and angled sliding doors			RST / PST
Folding doors			FTA
Special models		possible	possible
Operator height	108 / 150mm	108 / 150mm	> 150mm
Escape route systems RED ● / CO48 ● / TOS ●	●	● ● ●	● ● ●
<b>Optional equipment</b>			
Motorized bolt- ● or multi-point locking MPV ●	●	● ●	● ●
Profile system 20mm (up to 10mm single layer glass)	●	●	●
Profile system 32mm (up to 24mm insulating glass)	●	●	●
Foreign profiles up to 65mm	●	●	●
Door protective screen (designed entirely in glass)	●	●	●
Rechargeable battery for emergency opening ● or emergency operation ●	●	● ●	● ●
<b>Peripheral devices</b>			
record BDE-D remote control device with text display	●	●	●
record sensor systems	●	●	●
record diagnostic maintenance tool	●	●	●



STA 21

[www.agta-record.com](http://www.agta-record.com)



**record**

your global partner for entrance solutions

## record peripheral devices: sensors and remote control units

A decisive contribution to the success of our products is the fact that we are one of the few manufacturers of automatic doors that develops and makes both the hardware and software found in our control and sensor devices. This enables us to implement the improvements made by our developers and engineers in the most effective way possible by allowing the coordination of individual improvements on an on-going basis.

### Developed and manufactured entirely in-house

When analyzing its immediate environment, the record RAD 290 motion detector permanently communicates with the control device. The detection field is defined electronically, allowing it to eliminate previously acquired door movements. Time-consuming mechanical fine adjustment of the sensor is thereby eliminated. Also, changes to the field due to temperature differentials are largely uncritical.

The record RIC 290 sensor device uses both radar and infrared technologies. It is equipped with both motion and presence detectors that trigger opening and closing operations with a high level of security. The device actively communicates with the door control, and recognizes persons in the passage area. Several light curtains also prevent collisions with the door leaves.

The record AIR 290 is a pure active infrared motion and presence detector, ideally suited to delineated detection fields such as are found in lobbies and security interlocks.

### Remote control unit with text display

The electronic remote control device BDE-D is equipped with an illuminated display and features user-friendly, highly convenient menu navigation. Several operational modes are available to program basic door functions. These can be individually adjusted to make sure running characteristics meet specific needs. The ease of use is ensured by the clear menu structure, available in the local language.

### Sensors



radar-equipped motion detector RAD 290



motion and presence detector RIC 290



active infrared motion and presence detector AIR 290



flush-mounted model

### Remote control units



BDE-D (60 x 60 mm) with surface-mounted housing



Customized BDE-D with key-operated contact



BDE-D slim-line (44 x 92 mm)



Mechanical with key-operated switch

### Specifications

	record STA 21 – standard sliding doors (STA)		record STA 21 – telescopic sliding doors (TSA)	
	E-STA 1 leaf	D-STA 2 leaves	E-TSA 2 leaves	D-TSA 4 leaves
<b>Operator dimensions</b>	with cladding 194 x 108 / 150 mm without cladding 157 x 108 / 150 mm		with cladding 259 x 108 / 150 mm without cladding 222 x 108 / 150 mm	
<b>Door movement</b>	1.5 s to 0.7 m	1.0 s to 0.7 m	1.5 s to 0.7 m	1.0 s to 0.7 m
<b>Mass</b>				
<b>Power supply</b>	230V / 50 / 60Hz			
<b>Power consumption</b>	85W in operation / 25W in idle mode			
<b>Ambient temperature</b>	-15°C to +50°C			
<b>Remote control</b>	Electronic with illuminated display (record BDE-D)			
<b>Operational modes</b>	<ul style="list-style-type: none"> <li>→ Automatic operation</li> <li>→ Continuously open</li> <li>→ Manual operation</li> </ul>		<ul style="list-style-type: none"> <li>→ One-way traffic</li> <li>→ Locked</li> </ul>	
<b>Programmable functions</b>	<ul style="list-style-type: none"> <li>→ Customer-specific door parameters</li> <li>→ Control lock</li> <li>→ Bell contact</li> </ul>		<ul style="list-style-type: none"> <li>→ Emergency opening and closing (programmable parameters)</li> <li>→ Energy-saving function (automatic entrance widening TOWA)</li> </ul>	
<b>Options</b>	<b>Sensor, safety and security</b> <ul style="list-style-type: none"> <li>→ Bolt locking device VRR 20</li> <li>→ Motion detector RAD 290</li> <li>→ Motion and presence detector AIR 290</li> <li>→ Multi-purpose sensor RIC 290</li> <li>→ Floor safety rail</li> <li>→ Floor lock</li> <li>→ Key operated switch SSK</li> <li>→ CO48 escape route door system (France)</li> <li>→ Protective screen</li> </ul>		<b>Additional equipment</b> <ul style="list-style-type: none"> <li>→ Optical locking display</li> <li>→ Emergency-open button</li> <li>→ Manual unlocking inside and outside of door</li> <li>→ Battery for emergency operation during power failure</li> <li>→ Locking device surveillance</li> <li>→ Detachable operator housing</li> </ul>	
<b>Assembly variants</b>	→ Lintel-mounted, free standing or on the ceiling			

## Inspection and Maintenance Services

We have been manufacturing and marketing automatic door systems since 1953. The very first applications were to operate doors in laundries, but automatic door drives rapidly developed into attractive entrance systems with very different functional principles, initially driven by time-saving needs. Later came the prestige element, and today our door systems enhance the architecture of any building, actively contributing to its security and safety, and saving energy by reducing heating and air conditioning costs.

In the course of these developments, our products have become increasingly more refined, their functionality more comprehensive and their operation more convenient and user-friendly. At the same time, the legal requirements have become more demanding in order to enhance operational safety.

### The right service package for your needs

Today there are over 8000 record automatic door systems installed all over Switzerland, our home market, still operating smoothly, even after 20 years or more! Our customers use them every day and this enhances their satisfaction. Reliability such as this is only possible with a combination of clear aims and goals, the highest standards of design, construction and installation, and long-term maintenance by record's highly skilled in-house service technicians.

For your automatic door to function smoothly over decades and be able to fulfil the relevant safety and security regulations, periodic servicing and maintenance is unavoidable. Benefit from the flexibility of a record maintenance contract, which will allow you to vastly reduce your operational and maintenance costs.

### Your nearest record partner

Inspection and maintenance have a particularly high priority at record. The fact that record products are designed and built to last a long time also means they face changing legal requirements. To avoid unpleasant situations for our customers, we make it our priority to personalise our service and maintenance packages, enabling you to fully meet your legal requirements of due diligence.

In consultation with you, our advisor will find the ideal maintenance and service package to meet all your needs.

To know more, please get in touch with your record partner!

#### → record UK limited

Head Office: Garrion Business Park, Smith Avenue – Wishaw, ML2 0RY – UK

Central Office: 450a Bradford Road – Batley, WF17 5LW – UK

Southern Office: 17 Invincible Road – Farnborough, GU14 7QU – UK

tel.: +44 1698 376411 – info@recorduk.co.uk – www.recorduk.co.uk

#### → record international

record international ltd – Allmendstrasse 24 – 8320 Fehraltorf – Switzerland

tel.: +41 44 954 91 91 – e-mail: international@agta-record.com – www.agta-record.com

#### → Headquarters

agta record ltd – Allmendstrasse 24 – 8320 Fehraltorf – Switzerland

tel.: +41 44 954 91 91 – e-mail: info@agta-record.com – www.agta-record.com



www.agta-record.com



**record**  
your global partner for entrance solutions